International Application No.: PCT/JP2004/018051

U.S. Patent Application No.: Unknown

May 2, 2006 Page 4 of 7

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

Claim 1 (original): A transistor comprising:

a source electrode and a drain electrode arranged in mutually opposing relation;

a semiconductor film comprising at least one layer disposed between the source electrode and the drain electrode:

a gate electrode disposed in adjacent relation to the semiconductor film; and

a gate insulating film disposed between the gate electrode and each of the source electrode, the drain electrode, and the semiconductor film, wherein

a concentration of fluorine contained in the gate insulating film is 1 x 10^{20} atoms/cm 3 or less.

Claim 2 (original): The transistor of claim 1, wherein the concentration of the contained fluorine is 1 x 10¹⁹ atoms/cm³ or less

Claim 3 (original): The transistor of claim 1, which is of a field-effect type.

Claim 4 (original): The transistor of claim 1, wherein the gate insulating film is an amorphous silicon nitride film.

 $\label{eq:claim 5} \mbox{Claim 5 (original): The transistor of claim 1, \mbox{ wherein the gate insulating film is deposited by a CVD method.}$

Claim 6 (original): A CVD apparatus used to deposit the gate insulating film in the transistor of claim 1, the CVD apparatus comprising:

an electrode having a plurality of gas supply holes and disposed in a reaction chamber, wherein

International Application No.: PCT/JP2004/018051

U.S. Patent Application No.: Unknown

May 2, 2006 Page 5 of 7

a surface of the electrode is composed of a non-porous layer.

Claim 7 (original): A transistor comprising the gate insulating film deposited by using the CVD apparatus of claim 6.

Claim 8 (currently amended): A liquid crystal display device comprising the transistor of any one of claims 1, 2, 3, 4, 5, and 7 as a switching element for a pixel electrode portion.